## **Climate Pro Series Spot Coolers**



## **Climate Pro X14**

## Small but mighty spot cooling for factory and warehouse.

Taking a mere 4.4 sq. ft. of floor space, the Climate Pro X14 keeps people comfortable and productive with 13,200 Btu/h of cooling.

- Frugal with power. Runs on 115V with 15 amp circuit - uses just 1.3 kW.
- Extensive cooling reach.
- Provides effective temperature control in conditions from 70° to 113°F

13,200 Btu/h

1 Phase, 115V

**Cooling Capacity** 

IFI	iase,
Volta	ge



Electronic Features	
Control Panel	Programmable
Thermostat Control	Electronic
Cooling Capacity	
Rating Conditions: 95°F @ 60% RH	13,200 Btu/h
Electrical Characteristics	
Voltage Requirement	1 Phase, 115 V
Total Power Consumption	1.3 kW
Current Consumption	11.5 amps
Recommended Fuse Size	15 amps
NEMA Plug Configuration	5-15P
Min Max. Voltage	104 - 127 V
Fans	
Motor Output	0.23 kW
Evaporator	
Fan Type	Centrifugal
Max. Air Flow - High/Mid/Low	440/410/385 CFM
Max External Static Pressure	0.31 IWG



Condenser	
Fan Type	Centrifugal
Max Air Flow - High/Mid/Low	830/770/720 CFM
Max. External Static Pressure	0.19 IWG
Compressor	
Туре	Hermitic Rotary
Output	0.75 kW
Refrigerant	
Туре	R-410A
Dimensions	
WxDxH	22 x 29 x 48 in
Weight	
Net / Shipping	165 / 212 lb
Power Cord	
Gauge	14 AWG (3-core)
Length	10 ft
Condensate Tank	
Capacity	5 gal
Operating Conditions	
Min Max. @ 50% RH	70° - 113°F
Max. Duct Length	
Per Cold Duct Hose	30 ft
Hot Duct Hose	60 ft
Max. Sound Level	
With Condenser Duct - High/Mid/Low	57/56/55 dB(A)
Without Condenser Duct - High/Mid/Low	60/59/58 dB(A)