



OWC6012 Water-Cooled 5-Ton Deluxe Portable Water-Cooled Air Conditioner

Product Features:

- Solid State Electronic Controller
- Manual or Auto 6-Speed Fan Control
- Large LED Display
- Swivel Ball Bearing Casters with Locking Fronts
- Internal Condensate Pump with Overflow Alert
- Water Regulating Valve
- High Pressure Safety Switch
- Washable Electrostatic Air Filter

Technical Specifications:

Cooling Capacity	60,100 BTUH
Voltage	208-230V, 60Hz, 1PH
Amps	23.7
Total Watts	5000
Cooling Ambient	Operating Range 65° to 105°
Outdoor Use	No
Cooling Capacity	Total BTUH at 80°DB/67°WB Return air with 85°EWT and 105°LWT.
In Rush Amps	165
Plug Type	6-30P
EER	12.0
NOTE: Dedicated circuit and time delay fuses/circuit breakers are recommended.	
Compressor	Scroll
Compressor HP	5
Compressor LRA	158

EVAP CFM - High 1950

EVAP Motor HP 1

Water Line Connections

Water In 5/8 MF

Water Out 5/8 MF

Drain 3/8 MF

Condensate Removal Pump Automatic
20' Vertical Lift

Refrigerant Charge 52 oz R-410A

Height 53.2"

Width 28.2"

Depth 29.2"

Net Weight 375 lbs

Estimated Condenser Water Usage*

Entering Water Temp:

Condensing Water at 60° 3.8 GPM

Condensing Water at 85° 15 GPM

* Condenser Water Usage is base on 80/67 Ambient, and incoming water temperatures as shown. Usages will vary with water conditions and ambient temperatures.