

## Climate Pro K60

Five tons of dependable spot cooling for people and electronics.

Taking slightly less than 12 sq. ft. of floor space, the Climate Pro K60 brings temperatures under control with 60,000 Btu/h of cooling capacity. It's ideal when your application calls for a bigger response to keep employees and electronics from overheating.

- Powerful performance. Runs on 208/230V 60 Hz with 50 amp circuit and uses 6.6 kW.
- Dual condensers for effective cooling in temperatures from 65° to 105°F.
- Integrated condensate pump sends collected water to the drain — no tanks to empty.



**16,800 Btu/h**

Cooling Capacity

**1 Phase, 115V**

Voltage

### Electronic Features

Control Panel

Programmable

### Cooling Capacity

Rating Conditions: 95°F @ 60% RH

60,000 Btu/h

### Electrical Characteristics

Voltage Requirement

1 Phase, 208/230 V

Total Power Consumption

6.6 kW

Current Consumption

31.5 amps

Recommended Fuse Size

50 amps

NEMA Plug Configuration

6-50P

Min. - Max. Voltage

198 - 253 V

### Fans

Motor Output

0.23 kW Evaporator | 0.30 kW x 2 Condensers

### Evaporator

Fan Type

Centrifugal

Max. Air Flow - High/Mid/Low

1770/1710/1650 CFM

Max External Static Pressure

0.9 IWG

<b>Compressor</b>	
Type	Hermetic Rotary
Output	3.45 kW
<b>Refrigerant</b>	
Type	R-410A
<b>Dimensions</b>	
W x D x H	31 x 55 x 64 in
<b>Weight</b>	
Net / Shipping	582 / 683 lb
<b>Power Cord</b>	
Gauge	6 AWG (3-core)
Length	6 ft
<b>Condensate Tank</b>	
Auto Pump	Included
<b>Operating Conditions</b>	
Min. - Max. @ 50% RH	65° - 105°F
<b>Max. Duct Length</b>	
Per Cold Duct Hose	40 ft
Hot Duct Hose	100 ft
<b>Max. Sound Level</b>	
With Condenser Duct - High/Mid/Low	69/68/57 dB(A)
Without Condenser Duct - High/Mid/Low	71/70/69 dB(A)